

Open Door



REVISIONS

REV.	DESCRIPTION	DATE	BY
Model No.	U-208SS		
RoHS Compliance	Yes		
Form factor	2U		
Standard Drive Bays	3.5" Drive (internal): 1 Hotswap 3.5": 8 Slim DVD: 1 2.5" Drive (internal): 1		
Hotswap HDD Type	2.5" & 3.5" SAS I/II/III/4 & SATA I/II/III		
Indicators	Power + Fan Failure + HDD LED		
Switches	Power, Reset, Mute		
Expansion Slots	x 7 (Low profile)		
Material of Handle	Heavy-duty SGCC Cold-rolled Steel		
Material of Main Chassis	Heavy-duty SGCC Cold-rolled Steel		
Motherboard Size	12" x 10.5" (ATX, microATX)		
Cooling Fan	3 x 80mm		
Dimensions(W x H x D)	19.00" x 3.46" x 22.78" 482.0mm x 88.0mm x 578.7mm		
Backplane Type	miniSAS SFF-8087 6Gb/s		

Sliding Rail

R-201

1,



2,

RP-RAIL-26-1UB

PROPRIETARY AND CONFIDENTIAL
THE INFORMATION CONTAINED IN THIS DRAWING IS THE SOLE PROPERTY OF ISTARUSA GROUP. ANY REPRODUCTION IN PART OR AS A WHOLE WITHOUT THE WRITTEN PERMISSION OF ISTARUSA GROUP IS PROHIBITED.

		DIMENSIONS ARE IN MM		NAME		DATE	
		TOLERANCES:		DRAWN			
		FRACTIONAL ±		CHECKED			
		ANGULAR: MACH ±		ENG APPR.			
		TWO PLACE DECIMAL ±		MFG APPR.			
		THREE PLACE DECIMAL ±		Q.A.			
		MATERIAL		COMMENTS:			
NEXT ASSY	USED ON	FINISH					
BY	UA						

iStarUSA®

U-208SS

SIZE	DWG. NO.	REV.
A	Draw1	
SCALE:1:1	WEIGHT:	SHEET 1 OF 1