


IS-200RSH1UP

200W 1U Redundant 1+1 Power Supply



Features

- Active PFC, Power Factor ≥ 0.95
- Hold up Time: 17ms at 100% Load
- 5 Output Rails
- Front Access Ability
- Power Failure Alarm
- Over Current Protection
- Over Voltage Protection
- Short Circuit Protection

Specifications

Model Number	Efficiency
IS-200RSH1UP	80%
RoHS Compliance	Connector Type
YES	Main Connector :: 24 pin/ 4pin 12V :: 1/ 8pin EPS 12V :: 1/ Molex :: 2 SATA :: 2/ Floppy :: 1
Output Wattage	Dimensions (WxHxD)
200	Width 4.17" (105.9 mm) Height 1.63" (41.4 mm) Depth 10.63" (270.0 mm)

Front View



Side View






Rear View



We at iStarUSA Group offer OEM/ODM services for Industrial Power, Custom Power, Chassis, Cabinets, and Data Storage. Through our skilled metal bending, milling, and silk screening we can provide you with unique customizations that will make your product stand out from the rest. With iStarUSA Group's OEM/ODM Solutions you can be sure to receive one-of-a-kind products for your one-of-a-kind business.

Dimensions



Compatible Chassis

* Please visit our website www.istarusa.com/en/xeal for a full list of compatible chassis

Output Rating

Output Voltage	+5V	+3.3V	+12V	-12V	+5VSB
Max. Load	20A	20A	16A	0.5A	2A
Min. Load	1A	1A	2A	0A	0.1A
Max. Combined	120W				
Total Output	184W			6W	10W